

ATTACHMENT / HANDLE

SC900FC (Heavy Duty)

**CONFORMITY WITH
EN ISO 5172**
Lengths available: 36", 48"

Features:

- Cuts up to 200 mm
- Straight Cutting Torch Built-in flashback Arrestors and Check valve for added safety
- Used with 1-101, 1-GPN series Cutting tips

T0069
Replacement Cartridge



"BUILT-IN" REVERSE
• Flow check valves for added
operator safety no need for
accessory check valves

SC1600C (Heavy Duty)

**CONFORMITY WITH
EN ISO 5172**

FEATURES

- Cuts up to 250 mm steel
- Die-forged head and ribbed handle made of brass.
- Universal mixer and smooth cutting oxygen valve.
- Used with 1-101, 1-GPN series Cutting tips

**CONFORMITY WITH
EN ISO 5172**

FEATURES

- Cuts up to 200 mm • Welds up to 12.7 mm
- Attached quickly and simply to 315FC, H315FC, 310C torch handle
- Head and body made from drop forged brass
- Supreme seamless stainless steel tube and needle valves
- HP seat install from bottom of body for easy repairing
- H315FC, 315FC Built-in Check valves and flashback arrestors



315FC (Heavy Duty)



CA2460 (Heavy Duty)



H315FC (Extra Heavy Duty)



310C (Heavy Duty)

ATTACHMENT / HANDLE

SCI620 (Heavy Duty)

SCI620L

**CONFORMITY WITH
EN ISO 5172**

Lengths available: 36", 48", 60"

Features:

- Cuts up to 300 mm
- Nozzle mixing for highest operator safety
- Used with SC12, SC50 series Cutting tips

**CONFORMITY WITH
EN ISO 5172**

FEATURES

- Cuts up to 200 mm steel
- Efficient Universal Spiral Head Mixer
- Inline stainless tubes for better visibility

- Ergonomic, textured, precision contoured handle is designed to reduce operator fatigue and provide better grip
- Durable to withstand tough use and prevention of dents and scratches
- Intuitive color coded knobs



CA4II (Heavy Duty)



WH4IIC (Heavy Duty)

**CONFORMITY WITH
EN ISO 5172**

FEATURES

- Cuts up to 150 mm steel
- Attached quickly and simply to torch
- Handle 100FC, WH100, Head and body made from drop forged brass
- Supreme seamless stainless steel tube and needle valves



100FC (Medium Duty)

Build-in flashback
arrestor and check
valves



CA1350 (Medium Duty)



WH100 (Medium Duty)

CUTTING ATTACHMENT / TORCH HANDLE

SC62-3 (Heavy Duty)

SC62-5
(Heavy Duty)

Angle optional



HCW-38PC

CONFORMITY WITH EN ISO 5172

FEATURES

- Triangular stainless steel gas tubes for maximum strength
- Two stainless steel needle valves for precise flame adjustment and better durability
- Built-in safety plug in torch head
- Stable flame preheating during cutting
- Simple structure for easy maintenance 90° Head (70° & 180° are available)
- Use with 6290,6290NX series cutting tips

CONFORMITY WITH EN ISO 5172

FEATURES

- Cuts up to 200 mm steel
- Welds up to 50 mm
- Attached quickly and simply to torch
- Handle WH63-2, WH43-2, Head and body made from drop forged brass
- Supreme seamless stainless steel tube and needle valves



CA73-3 (Heavy Duty)



WH63-2

W/Check valves



WH43-2

Stainless steel tube 28"



2396-28



5H

4H

3H

2H



E-43

WH43-2

CONFORMITY WITH EN ISO 5172

FEATURES

Soldering, brazing, annealing, straightening and bending plates, pipes and bars, preheating in welding jobs, drying moulds, thawing jobs, asphalt work etc...

HAND CUTTING TORCHES

SC250



Head Angle Optional:



CONFORMITY WITH EN ISO 5172

- Length available: 500mm, 900mm, 1200mm, 1500mm

Absolute Safety

- High resistance to back fires

Tough

- 90° Solid Forged Brass Head

Balanced Weight

- Comfortable working for continuous operation



Durable

- Rugged design ensures maximum strength

Accurate

- Precise flow rates

- Heavy duty applications even at low cylinder pressures

Excellent Cutting Quality

- Reduced Post Cut

- Grinding Operation



SC250-R (Net Weight: 1.22kg)

CONFORMITY WITH EN ISO 5172

- FEATURES

- Cuts up to 300 mm steel

- Used with PNME, ANME series tips

- Ryval 18°/90° NM250



SC250-U (Net Weight: 1.16kg)

CONFORMITY WITH EN ISO 5172

- FEATURES

- Cuts up to 300 mm steel

- Used with PNME, ANME series tips

- Universal 18°/90° NM250



SC250-B
Economical 18°/90° NM250

Net Weight Optional:
1.24kg
1.07kg
0.98kg



SC250-P

ATTACHMENT / HANDLE

CONFORMITY WITH EN ISO 5172

FEATURES

- Cuts up to 200 mm steel
- Welds up to 9 mm
- Attached quickly and Simply to WHX21



CONFORMITY WITH EN ISO 5172

FEATURES

- Cuts up to 300 mm steel
- Used with PNME, ANME series tips
- Messer type



CONFORMITY WITH EN ISO 5172

FEATURES

- Cuts up to 300 mm steel
- Used with PNME, ANME series tips
- Messer type



CONFORMITY WITH EN ISO 5172

FEATURES

- Cuts up to 300 mm steel
- Used with PNME, ANME series tips
- Messer type



CONFORMITY WITH EN ISO 5172

FEATURES

- Cuts up to 300 mm steel
- Used with PNME, ANME, 102, 106 series tips
- Gentec type

ATTACHMENT / HANDLE

CONFORMITY WITH EN ISO 5172

FEATURES

- Cuts up to 75 mm steel
- Welds up to 6 mm
- Attached quickly and Simply to WH261
- Used with AFN Tips



CA260 (Light Duty)



UNI-30



WH261 (Light Duty)

CONFORMITY WITH EN ISO 5172

FEATURES

- Cuts up to 200 mm steel
- Welds up to 9 mm
- Attached quickly and Simply to WH264 and WH265
- Used with PNME, ANME Tips



CA262 (Heavy Duty)



UNI-50



WH264 (Heavy Duty)



WH265 (Heavy Duty)

CONFORMITY WITH EN ISO 5172

FEATURES

- Cuts up to 200 mm steel
- Welds up to 9 mm
- Attached quickly and Simply to WH310 and WH311
- Used with PNME, ANME Tips
- AFROX Type



CA312 (Heavy Duty)



AF-313



WH310 (Heavy Duty)



WH311 (Heavy Duty)

ATTACHMENT / HANDLE

CONFORMITY WITH EN ISO 5172

FEATURES

- Cuts up to 75 mm steel
- Welds up to 6 mm
- Solid forged handles gun drilled
- Simple hand connections for changes from welding to cutting



CA266 (Light Duty)



UNI-10



WH267 (Light Duty)



WH268 (Light Duty)

CONFORMITY WITH EN ISO 5172

FEATURES

- Cuts up to 200 mm steel
- Welds up to 9 mm
- Attached quickly and Simply to WH270 and WH271



CA269 (Heavy Duty)



UNI-20



WH270 (Heavy Duty)



WH271 (Heavy Duty)

CONFORMITY WITH EN ISO 5172

FEATURES

- Cuts up to 75 mm steel
- Welds up to 6 mm
- Attached quickly and Simply to WH274



CA272 (Light Duty)



UNI-30



WH274 (Light Duty)

CONFORMITY WITH EN ISO 5172

FEATURES

- Cuts up to 200 mm steel
- Welds up to 9 mm
- Attached quickly and Simply to WH276



CA275 (Heavy Duty)



UNI-40



WH276 (Heavy Duty)

ATTACHMENT / HANDLE

SCI610 (Heavy Duty)



CONFORMITY WITH EN ISO 5172

FEATURES

- Cuts up to 300 mm steel
- Head Mixing for highest operator safety
- Built-in safety plug in torch head
- Used with 1502, 1503 series cutting tips

SCI610L



"BUILT-IN" REVERSE --
• Flow check valves for added
operator safety no need for
accessory check valves

SCI611 (Heavy Duty)

CONFORMITY WITH EN ISO 5172

FEATURES

- Cuts up to 200 mm steel
- Attached quickly and simply to torch Handle WH201
- Head and body made from drop forged brass
- Supreme seamless stainless steel tube and needle valves



CA2850 (Heavy Duty)

CONFORMITY WITH EN ISO 5172

- Used with 201-W series welding tips



WH201 (Heavy Duty)

CONFORMITY WITH EN ISO 5172

- Used with 200-W series welding tips



WH200 (Light Duty)



200-W

Model	GAS	Tip Size	Length mm	Order #
200AC-2	ACETYLENE	2	100	0.9
200AC-4		4	100	0.9
200AC-6		6	100	1.1
200AC-8		8	100	1.2
200AC-12		12	100	1.3
200GLP-2	PROPANE	2	100	1.2
200GLP-4		4	100	1.3
200GLP-6		6	200	1.7
200GLP-8		8	210	2.2
200GLP-12		12	210	2.4



201-W

Model	GAS	Tip Size	Length mm	Order #
201AC-2	ACETYLENE	2	154	0.9
201AC-4		4	154	0.9
201AC-6		6	212	1.1
201AC-8		8	220	1.2
201AC-12		12	220	1.3
201GLP-2	PROPANE	2	184	1.2
201GLP-4		4	154	1.3
201GLP-6		6	212	1.7
201GLP-8		8	220	2.2
201GLP-12		12	220	2.4

ATTACHMENT / HANDLE

SCI630 (Heavy Duty)



SCI630L

CONFORMITY WITH
EN ISO 5172

FEATURES

- Cuts up to 300 mm steel
- Torch length: 460-2000mm
- Head Angle Optional: 90°, 180°

- Triangular stainless steel gas tubes for maximum strength
- Two stainless steel needle valves for precise flame adjustment and better durability
- Head mixing for highest operator safety 90° Head (180° are available)
- Use with 41,44 series cutting tips

CONFORMITY WITH
EN ISO 5172

FEATURES

- Cuts up to 150 mm steel
- Welds up to 9 mm
- Two stages control valves seat ensure supreme flame control and working safety



CA242 (Heavy Duty)




CA242-180°



Handle color can
be customized

WH241 (Heavy Duty)



CR0024

Roller Guides And Circle
Cutting Attachment



WH281

ACETYLENE

SW282A (Light Duty)



WH281

LPG

SW282P (Light Duty)